



**Kinotech Industry**

Galati - Romania

TEL./FAX: 0236-466.372

TEL./FAX: 0236-313.013

www.kinotech.ro

E-mail: office@kinotech.ro

Mobil: 0768-463.636

Mobil: 0723-694.919

Mobil: 0765-998.277

Mobil: 0766-360.062

## Parama sintetica TK

### Specificatii tehnice

Material: poliester si polipropilena

Standard: EN 919; EN 10556

Constructie: 8 fire impletite (4x2)

Utilizari: remorcare, offshore

Certificari: Lloyd`s Register si GL



Diametru (mm)	Greutate (g/m)	Rezistenta (kg)	Rezistenta (kN)
36	717	29100	285,5
40	885	35860	351,8
44	1070	42990	421,8
48	1270	49950	490
52	1500	57800	567
56	1730	66180	649,3
60	1990	75640	742
64	2270	85630	840
68	2560	95960	941,3
72	2870	107570	1055,3
76	3200	119880	1176
80	3540	132190	1296,8
88	4280	158590	1555,8
96	5100	183990	1805

Densitate	1.14 g/cm <sup>3</sup>
Flotabilitate	NU
Temperatura maxima	120°C
Rezistenta UV	Foarte buna
Rezistenta la acizi	Buna
Rezistenta la baze	Buna
Rezistenta la solventi organici	Foarte buna