


Small lifting eye, grade 8

- **Material** : alloy steel, grade 8, quenched and tempered
- **Safety factor** : MBL equals 4 x WLL
- **Finish** : painted red
- **Certification** : at no extra charge this product can be supplied with a works certificate, a 3.1 certificate and/or EC Declaration of Conformity



Dimensions table

Code	WLL	Ø ISO	Dimensions in mm					Assembly With	BF	Weight
			A	B	C	D	E		t	Kg
OL 8	0.50	M8	6	8	13	30	26	XLC0 CO5/6 CSC5/6	2.0	0.05
OL 10	0.90	M10							3.6	0.06
OL 12	1.25	M12							5.0	0.07
OL 14	1.50	M14	8	10	17	45	29	XLC1 CO7/8 MP7/8 CSC7/8	6.0	0.13
OL 16	1.90	M16							7.6	0.15
OL 18	2.25	M18							9.0	0.17
OL 20	3.12	M20	10	13	20	55	37	XLC2 CO10 MP10 CSC10	12.5	0.28
OL 22	3.80	M22							15.2	0.31
OL 24	5.00	M24	12	16	29	67	49	XLC3 CO13 MP13 CSC13	20.0	0.59
OL 27	6.25	M27							25.0	0.65
OL 30	8.00	M30	14	20	35	90	54	XLC4 CO16 MP16 CSC16	32.0	1.07
OL 33	9.00	M33							36.0	1.17
OL 36	10.00	M36							40.0	1.29
OL 39	12.50	M39	19	24	40	105	69	XLC5 CO18/20 CSC18/20 MP18/20	50.0	2.00
OL 42	15.00	M42							60.0	2.16