



## Thimbles generally to DIN 3091 code S-6134

- **Material** : cast mild steel, (GTW 40)
- **Standard** : generally to DIN 3091
- **Finish** : self coloured
- **Certification** : a works certificate can be supplied upon request

| diameter rope | width groove | width | length | diameter | length | weight per 100 pcs |
|---------------|--------------|-------|--------|----------|--------|--------------------|
| mm            | a mm         | b mm  | c mm   | d mm     | e mm   | kg                 |
| 8             | 9            | 40    | 66     | 14       | -      | 18                 |
| 10            | 11           | 50    | 82     | 18       | -      | 32                 |
| 12            | 13           | 60    | 98     | 21       | -      | 52                 |
| 14            | 16           | 70    | 114    | 25       | -      | 80                 |
| 16            | 18           | 80    | 130    | 28       | 16     | 90                 |
| 18            | 20           | 90    | 145    | 31       | 18     | 121                |
| 20            | 22           | 100   | 161    | 35       | 20     | 161                |
| 22            | 24           | 110   | 177    | 38       | 22     | 211                |
| 24            | 26           | 120   | 193    | 41       | 24     | 271                |
| 26            | 29           | 130   | 209    | 44       | 26     | 355                |
| 28            | 31           | 140   | 224    | 47       | 28     | 420                |
| 32            | 35           | 160   | 256    | 53       | 32     | 630                |
| 36            | 40           | 180   | 288    | 59       | 36     | 884                |
| 40            | 44           | 200   | 320    | 65       | 40     | 1100               |
| 44            | 48           | 220   | 352    | 70       | 44     | 1500               |
| 48            | 53           | 240   | 384    | 76       | 48     | 2000               |
| 52            | 57           | 260   | 416    | 81       | 52     | 2500               |
| 56            | 62           | 280   | 448    | 86       | 56     | 3200               |
| 64            | 70           | 320   | 512    | 95       | 64     | 4600               |
| 72            | 79           | 360   | 576    | 104      | 72     | 6600               |
| 80            | 88           | 400   | 640    | 112      | 80     | 9000               |



S-6134

