









**ENDLESS ROUND SLINGS ACC. TO EN 1492-2**








- Safety factor 7 : 1
- Colour code acc. to EN 1492 - 2
- One black stripe per ton W.L.L.

colour	min NL m	max NL m	W.L.L.				
			 kg	 kg	 kg	 kg	 kg
violet	0.5	20	1000	800	2000	1400	1000
green	0.5	20	2000	1600	4000	2800	2000
yellow	0.5	50	3000	2400	6000	4200	3000
grey	0.5	50	4000	3200	8000	5600	4000
red	0.5	50	5000	4000	10000	7000	5000
brown	1.0	50	6000	4800	12000	8400	6000
blue	1.5	50	8000	6400	16000	11200	8000
orange	2.5	50	10000	8000	20000	14000	10000
orange	2.5	50	20000	16000	40000	28000	20000
orange	2.5	50	30000	24000	60000	42000	30000
orange	2.5	50	40000	32000	80000	56000	40000
orange	2.5	50	50000	40000	100000	70000	50000
orange	2.5	50	60000	48000	120000	84000	60000
orange	2.5	50	80000	64000	160000	112000	80000
orange	2.5	50	100000	80000	200000	140000	100000

**ENDLESS ROUND SLINGS WITH SLEEVE ACC. TO EN 1492-2**



- Safety factor 7 : 1
- Colour code acc. to EN 1492 - 2
- One black stripe per ton W.L.L.

colour	min NL m	max NL m	W mm	EL mm	W.L.L.				
					 kg	 kg	 kg	 kg	 kg
violet	0.5	10	35	150	1000	800	2000	1400	1000
green	0.5	10	40	200	2000	1600	4000	2800	2000
yellow	0.5	20	50	200	3000	2400	6000	4200	3000
grey	0.5	20	60	300	4000	3200	8000	5600	4000
red	0.5	20	70	300	5000	4000	10000	7000	5000
brown	1.0	50	75	400	6000	4800	12000	8400	6000
blue	1.5	50	86	400	8000	6400	16000	11200	8000
orange	2.5	50	100	500	10000	8000	20000	14000	10000
orange	2.5	50	130	600	20000	16000	40000	28000	20000