



## Steel Wire Rope Construction 6x36 WS– Steel Core


**Product description:** steel wire rope ungalvanised,

galvanised or stainless steel, steel core,

construction **6x36 Warrington Seale**.

**Application :** drilling, portal cranes, cranes, special equipment

**Standards:** DIN 3058, EN DIN 12385



### 6x36WS + IWRC

| Nominal Diameters | Approximate Weight | Minimum Breaking Strength [kN] |
|-------------------|--------------------|--------------------------------|
| [mm]              | [Kg/m]             | [1770N/mm <sup>2</sup> ]       |
| 14                | 0,802              | 124                            |
| 16                | 1,047              | 161                            |
| 18                | 1,325              | 204                            |
| 19                | 1,476              | 227                            |
| 20                | 1,636              | 252                            |
| 22                | 1,980              | 305                            |
| 24                | 2,356              | 363                            |
| 25                | 2,556              | 394                            |
| 26                | 2,765              | 426                            |
| 28                | 3,207              | 494                            |
| 30                | 3,681              | 567                            |
| 32                | 4,188              | 645                            |
| 34                | 4,728              | 728                            |
| 36                | 5,301              | 817                            |
| 38                | 5,906              | 910                            |
| 40                | 6,544              | 1.008                          |
| 42                | 7,215              | 1.112                          |
| 44                | 7,918              | 1.220                          |
| 46                | 8,654              | 1.333                          |
| 48                | 9,423              | 1.452                          |
| 50                | 10,225             | 1.575                          |
| 52                | 11,059             | 1.704                          |
| 54                | 11,926             | 1.837                          |
| 56                | 12,826             | 1.976                          |
| 58                | 13,759             | 2.120                          |
| 60                | 14,724             | 2.268                          |